

Xerox[®] Color J75 Press Produce high-value jobs and highly satisfied customers.



Xerox® Color J75 Press Specifications

Resolution

- Print/Copy: 2400 x 2400 dpi
 Scan: 200 x 200, 300 x 300, 400 x 400, 600 x 600
- Line Screens: 600, 300, 200, 150 Dot, 200 Line Screen, Stochastic Screen

Technology

- Automatic Color Quality Suite (ACQS)
- Load-while-run capability
- Advanced Registration Technology for tighter control
- Custom paper registration profiles
- Simplified Image Quality Adjustment (SIQA) Toolset
- Xerox® EA low melt Dry Ink
- SMart Kit® replaceable units for Dry Inks, drums, fuser, waste bottle, staples
- Active decurling for heavyweight media

Selected Color/Graphic Arts Credentials

 Fogra certification, PANTONE MATCHING SYSTEM, PANTONE Goe™, PANTONE PLUS, Adobe® PDF Print Engine

Integrated Scanner

- Color scanner
- Single pass duplex scanning
- Scan to a variety of output options
- 250 sheet capacity
- Up to 200 ipm (Color and Black and White)
- Originals up to 11" x 17" (A3) in weights from 38 gsm (16 lb bond) to 200 gsm (53 lb bond)
- Duplex Automatic Document Feeder (DADF)

Productivity/Print Speeds

- Duty Cycle: 450,000
- A4/76 ppm 8.5" x 11" 75 ppm (64 300 gsm)
- A3/11" x 17" 39 ppm (64 300 gsm)
- SRA3/12" x 18" 35 ppm (64 300 gsm)

Paper Flexibility/Weights

- Internal Trays 1-3: 550 sheet each, 18 lb bond to 80 lb cover (64 – 220 gsm) uncoated; 28 lb bond to 80 lb cover (106 – 220 gsm) coated
- Bypass Tray: 250 sheets, 18 lb bond 110 lb cover (64 – 300 gsm) uncoated; 28 lb bond – 110 lb cover (106 – 300 gsm) coated
- Coated, heavyweight, transparencies, DocuMagnet, labels, tabs; all trays run coated stock

Paper Format/Sizes

- Maximum sheet size all trays: 13" x 19.2"/ SRA3/330 x 488 mm
- Maximum print image area: 12.72" x 18.9"/ 323 x 480 mm
- Maximum copy image area: 11.6" x 16.8"/ 297 x 432 mm
- Minimum paper size trays 1-3: 5.5" x 7.2"/ 140 x 182 mm
- Minimum paper size bypass: 4" x 5.6"/ 100 x 148 mm
- Minimum paper size OHCF: 7.2" x 10"/B5/ 176 x 250 mm

Paper Capacity and Handling

- 1,900 sheets up to 13" x 19.2"/SRA3 standard via three internal trays and bypass tray
- Maximum paper capacity: 5,900 sheets 13" x 19.2" SRA3 via standard trays and two Oversized High Capacity Feeders (optional)
- 300 gsm/110 lb coated and uncoated automatic duplex (Oversized High Capacity Feeder recommended)

Options

- · Oversized High Capacity Feeder
- -18 lb bond -110 lb cover (64 -300 gsm)uncoated
- 28 lb bond 110 lb cover (106 300 gsm) coated
- 7.25" x 10.5"/184 x 267 mm/B5 to 13" x 19.2"/SRA3/330 x 488 mm
- One or two Tray Module: 2,000 sheets or 4,000 sheets
- Small media support included 2-OHCF

- GBC® AdvancedPunch
 - Punch configurations available in A4 and 8.5" x 11"
- Standard Finisher
 - 500 sheet top tray, 3,000 sheet stacker tray
- Multi-position hole punching and stapling
- Stapling, coated and uncoated, up to 100 sheets
- 200 sheet interposer for pre-printed and full bleed sheets
- Optional Folding Module for tri-fold and Z-fold
- Booklet Maker Finisher
 - All features of standard finisher
 - Coated/uncoated booklet bi-fold or saddle-stitched booklets
 - Up to 25 sheet (100 page booklet)
 - Optional Folding Module for tri-fold and Z-fold
- SquareFold® Trimmer Module
- Square fold up to 25 sheets
- Face trim between 2 20 mm in
 0.1 mm increments
- Paper weights 18 lb bond to 110 lb cover (64 – 300 gsm) coated and uncoated
- High Capacity Stacker
 - 500 sheet top tray
 - 4" x 5.6"/102 x 142 mm to 13" x 19.2"/SRA3
- 5,000 sheet main tray
- 7.2" x 10.5"/182 x 257 mm to 13" x 19.2"/SRA3

Choice of Print Servers

- Xerox® FreeFlow® Print Server
- Xerox® EX Print Server, Powered by Fiery®

Electrical

- Printer: 200 240 VAC 50/60 Hz
- Options: 100 240 VAC 50/60 Hz

Printer Dimensions

- Height: 54"/1,372 mm
- Width: 68"/1,714 mm
- Depth: 31"/777 mm



Xerox[®] Color J75 Press is certified by Fogra

Contact your Xerox representative for details to find out more about adding a bit of color to your business.

