

Xerox[®] Colour C60/C70 Printer Colour Multifunction Printer

To interactively build and configure your own Xerox[®] Colour C60/C70, please visit **www.buildyourownxerox.com**.





	Xerox [®] Colour C60 Printer		Xerox [®] Colour C70 Printer	
Simplex Speeds	Colour	Black and white	Colour	Black and white
8.5 x 11 in. / A4 64 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	Up to 60 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm	Up to 65 ppm Up to 65 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm	Up to 70 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm	Up to 75 ppm Up to 75 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm
11 x 17 in. / A3 64 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	Up to 30 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm Up to 14 ppm	Up to 33 ppm Up to 33 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm	Up to 35 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm Up to 17 ppm	Up to 37 ppm Up to 37 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm
12 x 18 in. / SRA3 64 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	Up to 27 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 29 ppm Up to 29 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm	Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 33 ppm Up to 33 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm
Auto Duplex Speeds	Colour	Black and white	Colour	Black and white
8.5 x 11 in. / A4 Example: 64 to 105 gsm uncoated	Up to 60 ipm 2-sided 30 sheets per minute	Up to 65 ipm 2-sided 32 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 75 ipm 2-sided 35 sheets per minute
11 x 17 in. / A3 Example: 64 to 105 gsm uncoated	Up to 30 ppm 2-sided 15 sheets per minute	Up to 33 ppm 2-sided 16 sheets per minute	Up to 35 ppm 2-sided 17 sheets per minute	Up to 37 ppm 2-sided 18 sheets per minute
Device Specifications				
Monthly Duty Cycle	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis). ¹			
Average Monthly Print Volume (AMPV)	10,000 to 50,000 pages per month ²			
Technology	Xerox® EA toner with Ultra Low Melt Technology (2400 x 2400 dots per inch)			
Control Panel Languages	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan			

Accessories				
Optional	Offset Catch Tray			
Optional	Offset Catch Tray High Capacity Feeder (A4)			
	1 Tray Oversized High Capacity Feeder with Stora	ge Bin		
	2 Tray Oversized High Capacity Feeder Interface Module			
	BR Finisher (includes Vertical Transport Kit) BR Booklet Maker Finisher (includes Vertical Transport Kit) C Fold / Z Fold Unit for BR Finisher or BR Booklet Maker Finisher			
	Standard Finisher (requires Interface Module) Standard Finisher with Booklet Maker (requires Interface Module) C/Z Folder for Standard Finisher (requires Interface Module and Standard Finisher with or without Booklet Maker) GBC® AdvancedPunch™ (requires Interface Module and Standard Finisher with or without Booklet Maker) Xerox® SquareFold® Trimmer Module (requires Interface Module and Standard Finisher with Booklet Maker) Convenience Stapler Xerox® EX-i C60/C70 Print Server Powered by Fiery®			
	Xerox® FreeFlow Print Server Integrated for the Xe			
	Xerox® EX C60/C70 Print Server Powered by Fiery® Foreign Device Interface Kit	0		
	Mobility Plate			
	Envelope Fuser Kit			
	USB Hub			
	XMPie® Variable Data Printing PostScript Kit (recommended for Xerox® Integrate	d Colour Server for the Xerox® Colour C60/C	70 – PostScript Kit not used with Fiery or FreeFlow Print	
	Servers)		· · · · · · · · · · · · · · · · · · ·	
	Media Card Reader			
	VOIP Fax 1 (3 Line Outside N. America) Fax Kits			
	Server Fax Kit			
	Common Access Card Enablement Kit			
	Xerox® Scan to PC Desktop® Xerox Secure Access Unified ID System®			
	Equitrac Office®			
Electrical Requirements				
North America	Voltage: 110-127V			
	Frequency: 50/60 Hz +/- 3%, 20 A			
Europe	Voltage: 220-240V			
	Frequency: 50/60 Hz +/- 3%, 10 A			
Accessories	Fach module requires 120V/1EA			
North America: Europe:	Each module requires 120V, 15 A Each module requires 220V, 10 A			
Power Consumption				
Running (Average)	C60: 1,052 watts; C70: 1,250 watts			
Sleep Mode (Average)	3 watts (Default time to Sleep mode = 2 min.)			
Low Power Mode Recovery Time	Less than 20 seconds			
Operating Environment	I			
Required Temperature Range	50° to 82° F / 10° to 28° C (Relative Humidity less	than 62.5% when temp is 32°C or less)		
Required Relative Humidity	50° to 82° F / 10° to 28° C (Relative Humidity less than 62.5% when temp is 32° C or less) 15% to 85% (no condensation)			
Sound Power Levels				
	Operating: 6.8 B(A); Standby: 3.6 B(A)			
Sound Pressure Levels	Operating: 56 dB(A); Standby: 18 dB(A)			
Weight (approximate base unit only)	604 lb., 273 kg			
Dimensions	Width	Depth	Height	
Base Unit with Offset Catch Tray	62 in. / 1,574 mm		54.8 in. / 1,391.5 mm	
Base Unit with BR Finisher	79.1 in. / 2,009 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm	
Base Unit with BR Booklet Maker Finisher	81.4 in. / 2,068 mm 31.6 in. / 803.5 mm 54.8 in. / 1,391.5 mm			
Base Unit with BR Booklet Maker Finisher and C Fold / Z Fold Unit	90.6 in. / 2,301 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm	
Base Unit with Standard Finisher	97.7 in. / 2481 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm	
Base Unit with Booklet Maker Finisher	122.9 in. / 3,121.7 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm	
GBC® AdvancedPunch™	12 in. / 305 mm 28.5 in. / 724 mm 38.5 in. / 978 mm			
Xerox [®] SquareFold [®] Trimmer	42 in. / 1,066.3 mm	28.5 in. / 724 mm	22 in. / 558.8 mm	
•	1			

High Capacity Feeder	15.3 in. / 389 mm	24.2 in. / 614 mm	14.8 in. / 377 mm	
One Tray Oversized High	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm	
Capacity Feeder		20.0 := /7(2)===		
Two Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm	
Certifications	1			
	WHQL certification (depending on p Citrix MEDITECH SAP Common Criteria (pending) ENERGY STAR® Environmental Choice EPEAT GS Mark NOM EAC/GOST To view the latest list of certification	rint server / controller selected) s, go to www.xerox.com/OfficeCertifications.		
Graphic Arts Credentials	to their the latest list of certification			
	FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3 [™] (certified) IDEAlliance Digital Press Certified to *requires an additional Print Server of			
Paper Handling				
Single-pass Automatic Document F	Feeder			
Capacity ³	250 sheets of plain paper – 20 lb. / 2	-		
Speed	Up to 200 ipm colour / 200 ipm blac	ck and white (2-sided, 8.5 x 11 in. / A4)		
Paper Sizes	Custom sizes: 5.5 x 8.5 in. to 11 x 17	7 in. / A5 to A3		
Weights	16 to 53 lb. bond / 38 to 200 gsm			
Bypass Tray	1			
Capacity ³	Up to 250 sheets			
Sizes	Custom sizes: 4 x 6 in. to 13 x 19 in.	/ 102 x 152 mm to 330.2 x 482.6 mm (A5 to SRA3)		
Weights	18 lb. bond to 110 lb. cover / 64 to 3	300 gsm (uncoated and coated)		
Envelope Capacity	30 to 50 envelopes			
Envelope Sizes		ult within tools) run flap open at the trail edge) 6.81 in. / 190 x 170 mm to 240 x 173 mm		
Envelope Weights	75 to 90 gsm			
Trays 1 to 4				
Capacity ³	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,140 sheets			
Sizes	Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / I Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / I	.5 to A3 B5, A4		
Weights	18 lb. bond to 80 lb. cover / 64 to 22 Trays 1 and 2: Up to 256 gsm unco	-		
Optional High Capacity Feeder (HC				
Capacity ³	2,000 sheets			
Sizes	7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x	266.7 mm, 279.4 x 215.9 mm (B5, A4)		
Weights	18 lb. bond to 80 lb. cover / 64 to 22	20 gsm (uncoated and coated)		
Optional Oversized High Capacity I	Optional Oversized High Capacity Feeder (OHCF) – 1 or 2 Tray Options			
Capacity ³	1 Tray OHCF: 2,000 sheets plus Store 2 Tray OHCF: 4,000 sheets	age Cabinet		
Sizes	-	0 mm (B5) to 13 x 19.2 in. / 330 x 488 mm (SRA3) 1m to 13 x 19.2 in. / 330 x 488 mm (SRA3)		
Weights	18 lb. bond to 110 lb. cover / 64 to 3	300 gsm (uncoated and coated)		

Total Capacity	
Standard Capacity	3,260 sheets (includes Bypass Tray and Trays 1-4)
Maximum Capacity	7,260 sheets (includes Bypass Tray, Trays 1-4 and Two-tray Oversized High Capacity Feeder)
Automatic Two-Sided	 80 lb. / 220 gsm auto duplex 110 lb. cover / 300 gsm manual duplex for all stocks from bypass trays and optional Oversized High Capacity Feeder
Finishing	
Offset Catch Tray	
Capacity ³	500-sheet stacking
Optional BR Finisher (Requires V	'ertical Transport Kit)
Capacity ³	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Optional BR Booklet Maker Finis	her (Requires Vertical Transport Kit)
Capacity ³	Offsetting Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in. / A3 / SRA3
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, 12 x 18 in., SRA3 supported
Optional C Fold / Z Fold Unit (Op	otional with BR Finisher and BR Booklet Maker Finisher)
Types	C Fold, Z Fold and Z Half Fold
Capacity ³	40 sheets
Sizes	C Fold and Z Fold: Letter – 8.5 x 11 in. / A4 SEF only Z Half Fold: Tabloid – 11 x 17 in. / A3 only
Weights	16 lb. to 24 lb. bond / 64 to 90 gsm
Output Tray	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold
Optional Standard Finisher (requ	uires Interface Module)
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm

Hole-punching			
North America: Europe:	2-3 Hole Punch 2-4 Hole Punch		
Luiope.	4 Hole Swedish Punch (Optional)		
Interposing Capacity			
Capacity:	200 sheets of 128 gsm		
Sizes:	5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 qsm		
Weights: Decurling	Included with Interface Module and Standard Finisher		
Decurring	Bidirectional with Auto and Manual settings		
Optional Standard Finisher with Bo	ooklet Maker (requires Interface Module)		
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 2,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4		
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3		
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm		
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm		
Hole-punching			
North America:	2-3 Hole Punch		
Europe:	2-4 Hole Punch 4 Hole Swedish Punch (Optional)		
Interposing Capacity			
Capacity:	200 sheets of 128 gsm		
Sizes:	5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5		
Weights:	18 lb. bond to 80 lb. cover / 64 to 220 gsm		
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings		
Booklet Making Capacity	Saddle-stitch 2 to 25 sheets of 79 gsm (uncoated)		
	Bi-fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in., 13 x 18 in. / A4, B4, A3, SRA3		
•	otional with Standard Finisher – requires Interface Module)		
Punch Configuration Sizes	8.5 x 11 in. / 216 x 279 mm to 13 x 19.2 in. / 330 x 488 mm		
Weights	20 lb. bond to 80 lb. cover / 75 to 216 gsm (uncoated and coated)		
	Wide selection of slide-in / slide-out GBC punch die sets available		
Optional Xerox [®] SquareFold [®] Trimr	ner Module (Optional with Standard Finisher – requires Interface Module)		
Capacity	5 to 20-sheet booklets (up to 80 imaged sides) at 24 lb. / 90 gsm 5 to 25-sheet booklets (up to 100 imaged sides) at 20 lb. / 80 gsm		
Sizes	Custom sizes: 8.5 x 11 in. to 13 x 18 in. / A4 to SRA3		
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm		
Convenience Stapler			
Capacity	50 sheets (24 lb. / 90 qsm media)		
Print			
Print Resolution			
	Up to 2400 x 2400 dpi		
Line Screens	600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected)		
Registration	 Advanced registration technology for tighter control Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity 		
	(Available with Xerox® EX C60/C70 Print Server Powered by Fiery® and Xerox® FreeFlow® Print Server Integrated for the Xerox® Colour		
	C60/C70 Printer) • + 1.2 mm front to back registration		
First-print-out Time	PS- A4 LEF Simplex Colour 10.4 seconds / Black and white 8.5 seconds		
•			
Print Features	 A true multifunction product – print, copy, fax and scan, including scan to PC, USB or email, and mobile printing Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt toner for a smooth, offset-like finish 		
	Makes mobile printing simpler and more convenient		
	• Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 300 gsm		
	• Xerox Extensible Interface Platform® (EIP) allows you to connect to third-party software solutions that you can access from the touch-screen of the device		
	• Your choice of servers to best fit your environment:		
	– Xerox® Integrated Colour Server for the Xerox® Colour C60/C70 Printer		
	 – Xerox® EX-i C60/C70 Print Server Powered by Fiery® – Xerox® FreeFlow® Print Server Integrated for the Xerox® Colour C60/C70 Printer 		
	– Xerox® FreeFlow® Print Server Powered by Fiery®		
	• Inline finishing options offer a professional polish with stapling, hole-punching, folding and booklet making for presentations, brochures, reports		
	and newsletters		
	 Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support 		

Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox devices in every new location. Plug into a new network and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Print Solutions			
Xerox® Mobile Print Cloud (Optional)	Xerox [®] Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft [®] Office [®] rendering and more. Print what you need, when, where and how you need it.		
Xerox® Mobile Print Solution (Optional)	Xerox [®] Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox [®] Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.		
Сору			
First-copy-out Time From the Platen: From the DADF:	As fast as 7.8 seconds colour / 5.1 seconds black and white As fast as 9.6 seconds colour / 5.3 seconds black and white		
Warm Up Time	90 seconds (from cold powered down to Ready Copy)		
Digital Imaging	Auto colourAuto rotationImage shiftEdge eraseAuto centreingOriginal type selection (photo and text, photo, text, map) with subtypesLighter/darkerBackground suppressionAuto and manual contrastSharpnessColour balance, colour shift and saturation		
Reduce / Enlarge	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable per centages		
Special Features	Auto paper select Auto paper select Auto tray switching Automatic job recovery Auto colour selection Poster mode Annotation Single/Dual colour Booklet creation Multi-up = 2, 4 or 8 up Repeat Image Mirror image Covers insertion (front and back, back only, blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Book capying Sample Job Mixed size originals Sheet Insert Stamping 2.1n-1 X Y Zoom Zoom Range 25 to 400% Margin Shift Photo Mode Preset Reduce / Enlarge Preset Reduce / Enlarge Preset, Image Repeat, Image Rotate Interrupt Job Build Job Divergramme		

Scan	
Concurrency	Scan while printing or while it is transferring scan to network or fax jobs
Scan Features	Mixed size originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job
Input Speed	Up to 200 images per minute colour and black and white
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
Maximum Scan Area	Originals up to 11 x 17 in. / A3
Network Print Services	Novell NDPS Novell Pserver / NDS Port 9100 RFC 1179 (LPR) Print to Mailbox and Release
File Formats	PDF Image Only PDF (Searchable) PDF (Linearised) PDF (A-1 Level A) TIFF V6 JFIF XPS
Document Management Fields (Metadata)	One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard
Scan Features	Scan to Desktop WIA Scan to Desktop TWAIN Scan to Desktop TWAIN Scan to Desktop TWAIN Scan to FTP Scan via NDS Scan via NDS Scan via NMB Scan via MB Scan via HTTP Scan via HTTPS Scan to USB Storage Device Scan to USB Storage Device Scan to Genste Printer Scan to Multiple Destinations Scan to Genste Printer Scan to Documentum Scan to Documentum Scan to Documentum Scan to Documentum Scan to Domino Scan to Domino Scan to Interwoven WorkSite Scan to Interwoven WorkSite Scan to Interwoven WorkSite Scan to Interwoven WorkSite Scan to Microsoft Dynamics GP Scan to Microsoft Portal Server Scan to Microsoft Network Folder Scan to Thompson ProLaw Scan to Thompson ProLaw
Supported Scan Destinations (Standard)	Scan to Email, Scan to Folder, to PC, to Mailbox (private and public)
Scan to Email Features	Colour scanning, Auto Colour, Greyscale, Black and white Direct document email from device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job
Supported Scan Destinations (Optional)	Options include Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview

Authentication	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox [®] ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox [®] MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.
Fax (Optional) – One or Three Line	Fax Options
Compatibility	Colour, Auto Colour, Black and white
Maximum Scan Area	11 x 17 SEF
Fax Send Features	iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination
Fax Print Features	Print from USB Storage Device Media Print Unicode Printing
Fax Features	IFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination
Device Management	
Xerox [®] CentreWare [®] Internet Servi	ces – Integrated Web Pages Provided by the Device
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese
Remote Services	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox [®] SuppliesAssistant [®]	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Xerox® MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting / repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.
Security	
Features	Secure Print IPsec HTTPS (SSL) Embedded Fax Port Blocking IPv6 Support IPv6 Support IPv4 and IPv6 Environments OS Security Updates 802.1X Support (IEEE Standard) Secure Login Network Authentication Xerox Secure Access Unified ID System® IP Address Restriction Job Audit Tray Data Encryption 128-bit AES Encryption 256-bit AES Encryption Image Overwrite Common Criteria (pending)

Xerox Secure Access Unified ID Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee / student ID PIN or badge System[®] (Optional) providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralised print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions. **Print Server** Xerox[®] Integrated Colour Server for the Xerox[®] Colour C60/C70 Printer Processor 993 MHz Memory (ESS) 4 GB RAM System Disk 320 GB Hard Disk Drive Display 10.4 in. colour touchscreen flat-panel **Device Operating System** VxWorks Page Description Languages PDF XPS®, PCL® 6 emulation HP-GL2 (direct submission) Adobe[®] PostScript[®] 3[™] option TIFF JPEG Windows[®] XP SP1 & above (32 & 64 bit) Operating Systems Server 2003 / 2008 (32 & 64 bit) Vista (32 & 64 bit) Windows 7 (32 & 64 bit) Mac OS® 10.4 and above Citrix[®] Custom driver for UNIX: – AIX® 5 v5.3 – HP-UX® 11.0 / 11i v2 - Solaris® 8/9/10 – Linux® Fedora Core® 1/5 – Red Hat® ES4 - SUSE® 10/11 Windows 2003/XP 32 Bit Print Drivers Supported Windows 2003/XP 64 Bit Windows Vista/Vista 32 Bit Windows Vista/Vista 64 Bit Windows 7 / 2008 32 Bit Windows 7 / 2008 64 Bit (Microsoft certified) Macintosh® OS 10.3.0 and UNIX N/A Bi-directional with Xerox Custom Xerox® Mobile Express Driver® XPS Print Driver Xerox® Global Print Driver® Features Automatic two-sided • Bi-directional Print Drivers provide device and job status • Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) Secure print Delay print • Embedded Web server for remote control/monitor/setup • Enhanced Gloss • Sample set Booklet creation • Cover selection • Paper selection by attribute • N-up • Watermarks Banner sheets • Fit to new paper size • Output tray selection • Print calibration • Print from USB Plus more! Connectivity Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec) For more information, go to www.xerox.com/C70IntegratedColorServer. Additional Print Server Options Xerox[®] EX-i C60/C70 Print Server Powered by Fiery[®] Intel® Pentium® G850 Processor, E200, 2.90 GHZ Processor Memory (ESS) 2 GB System Disk 500 GB Print Languages (PDL) Adobe® PostScript® 3™ (v3019), PCL 6C (emulation), Adobe Acrobat 9

Features	 Productivity starts with a fast RIP. The Integrated Fiery Colour Server enables you to print large and/or complex Microsoft® Office® documents, PowerPoint® files and colour-critical PDFs accurately and quickly. Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers. Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the pre-set drivers configured for the task. Get the colour right. Produce precise, exact colour from all applications, platforms and formats with Fiery colour management tools. Turn up the impact with variable information. Customise your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Colour Server's basic variable data printing capabilities.
Connectivity	Direct Connection (Single IP)
	For more information, go to www.xerox.com/C70EXiFieryColorServer.
Xerox [®] FreeFlow [®] Print Server Int	tegrated for the Xerox® Colour C60/C70 Printer
Processor	Intel® Dual Core Pentium G3420 Processor
Memory (ESS)	8 GB
System Disk	1 TB 7200 SATA or equal
Print Languages (PDL)	True Adobe® PostScript® Level 1, 2, 3; Adobe® Acrobat® 9.0, PDF 1.8, PDF/X; TIFF, PCL 5c, PCL 6XL, EPS, JPEG
Features	Simple Vindows 7 platform for a familiar experience Integrated / Bustled setup. Perfect for small footprint and quick and easy site setups Accepts Native Microsoft Office® files for Direct Print (from walk-up USB PowerPoint®, for example) Productive All the advantages of a Xerox Production workflow – delivered in a value-oriented solution Streamlined drag/drop submission from tablets and more Powerful Bring the power of Xerox® patented RIP technology in a value oriented solution Latest direct Adobe PDF Print Engine and GC credentials included Includes Variable Data Print / Colour Management / Production Workflows Tints and Highlights fine-tuned for better accuracy Duotone, Tri-tone and Quad-tone support
Connectivity	Direct Connection (Single IP)
	For more information, go to www.xerox.com/C70FreeflowPrintServer.
Xerox [®] EX C60/C70 Print Server P	Powered by Fiery®
Processor	Intel® Core i5-2400, 4 Core, PRO80-IV, 3.10 GHz
Memory (ESS)	4 GB
System Disk	1 TB
Print Languages (PDL)	Adobe PostScript® Level 1, 2, 3; PDF/X-1a, 3 and 4; EPS; Adobe Acrobat® 9.1, Native PDF 1.3, 1.4, 1.5, 1.6 and 1.7;
	CT/LW; TIFF, TIFF/IT, DCS2, JPEG Microsoft Native Formats (DOC, XLS, PUB, PPT) enabled through Fiery Hot Folders feature EFI™ FreeForm 1, and FreeForm 2 VDP
Features	CT/LW; TIFF, TIFF/IT, DCS2, JPEG Microsoft Native Formats (DOC, XLS, PUB, PPT) enabled through Fiery Hot Folders feature
Features	 CT/LW; TIFF, TIFF/IT, DCS2, JPEG Microsoft Native Formats (DOC, XLS, PUB, PPT) enabled through Fiery Hot Folders feature EFI™ FreeForm 1, and FreeForm 2 VDP Fiery technology increases your profits by delivering high-impact documents with vibrant images and colour that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production. With Fiery technology, you can produce effective marketing pieces with the widest range of output options, including automatic identification of job elements such as text, images and spot colours. This feature also eliminates the need to re-programme jobs, making the process simple and quick. It is ideal for producing powerful marketing materials, personalised communications and packaging and photo publishing applications. Fiery ColourWise gives high-quality colour out-of-the-box and integrates the essential components of Fiery Graphic Arts Package, Premium Edition, Fiery Spot-On and the Fiery Colour Profiler Suite to control and manage colour throughout your workflow. The Fiery Command WorkStation increases your production and reduces errors and waste by centralising job management via its intuitive user interface. Simplify your labour-intensive document composition and imposition tasks even more by using Fiery SeeQuence Impose and Compose's intuitive interface. Fiery JDF technology connects EFI solutions and Fiery-enabled solutions, so you can move job information through your system faster and more efficiently. By supporting the Adobe PDF Print Engine, Fiery servers also offer a native end-to-end PDF workflow, therefore improving the consistency and flexibility of your printed output from design to print. Using Fiery servers and Fiery Command Workstation, you get a new level of integration for process and profit improvement, including seamless

Supplies	Description	Yield	Part Number
Customer Replaceable Items			
Toner Cartridges (Metered)	Black	30,000 pages4	006R01521
	Cyan	34,000 pages4	006R01524
	Magenta	32,000 pages4	006R01523
	Yellow	34,000 pages4	006R01522
Toner Cartridges (Sold)	Black	30,000 pages4	006R01659
	Cyan	34,000 pages4	006R01660
	Magenta	32,000 pages4	006R01661
	Yellow	34,000 pages4	006R01662
Black Drum Cartridge	1 Cartridge	190,000 pages ⁴	013R00663
Colour Drum Cartridge	1 Cartridge per Colour	85,000 pages4	013R00664
Charge Corotron	For Black Drum	190,000 pages ⁴	013R00650
Fuser	110V 220V	200,000 pages ⁴ 200,000 pages ⁴	008R13102 008R13065
Waste Toner Container	1 Cartridge	50,000 pages4	008R12990
Feed Roll Kits	1 Assembly	300,000 pages4	008R13169
Staple Cartridges	For BR Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	For BR Booklet Maker Finisher (4 cartridges per carton)	5,000 each cartridge	008R13177
	Staple Cartridge and Waste Container for Standard Finisher	5,000 each cartridge	008R13041
Staple Refills	For BR Finisher, BR Booklet Maker Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill (15,000 total)	008R12941

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ Approximate pages. Declared Yield based on 5 page job size, 30% colour and 70% Black and white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.

To view a product video, visit www.xerox.com. Build and configure your own Xerox® Colour C60/C70 Printer at www.buildyourownxerox.com.

